

Miria M. Finckenor NASA/Marshall Space Flight Center

James M. Zwiener, Amy Alvis, Steve Jones, Ken Jones AZ Technology, Huntsville, AL

National Space and Missile Materials Symposium
Scottsdale, AZ
June 2010



# Materials on International Space Station Experiment (MISSE) - 6

Deployed: March 13, 2008 on STS-123

Retrieved: September 1, 2009 on STS-128

- Materials' Location on MISSE-6
- Environmental Exposure
- Effects on Coatings
  - Thermal Control Coatings
  - Marker / Astronaut Visual Aid Coatings
- Discussion and Conclusions





MISSE-6B Wake / Ram

Photo courtesy of Langley Research Center





Ram-facing - AZ93 w/Teflon, AZ93, TMS800IY/TMJ-20LSB, AMJ760/AMJ750, AMJ600IR AZ400, MLS85LSB conductive, MLS85LSB





Wake-facing – AZ400, AMJ-700-IBU, MLS85LSB, MLS85LSB conductive, AZ93, AZ93 w/Teflon, AZ93 on Kapton



# Environmental Exposure

# Ram-facing side


- ~2 x 10<sup>21</sup> atoms/cm<sup>2</sup> atomic oxygen (Kapton erosion)
- ~ 2,600 equivalent sun-hours UV

# Wake-facing side


- ~1.4 x 10<sup>20</sup> atoms/cm<sup>2</sup> atomic oxygen (Kapton erosion)
- ~ 1,950 equivalent sun-hours UV
- >8,400 thermal cycles of +40/-40 °C


















# MISSE-6 AZ93 with Teflon overcoat



Samples from MISSE-3 and -4 also ranged from 0.17 to 0.19 in solar absorptance




# MISSE-6 AZ93 on Kapton






# MISSE-6 AZ93 on beta cloth






## MISSE-5 AZ93 on Beta Cloth

**No Aluminization** 








Previously flown AZ93 on Beta Cloth on MISSE-5. Change in reflectance spectra may indicate darkening of beta cloth underneath coating.

MISSE-6 AZ93 applied slightly thicker.




# MISSE-6 AZ400 conductive white






# MISSE-6 MLS-85-SB






# MISSE-6 MLS-85-SB conductive black











# **Marker Coatings**

Comparison between MISSE-5 and MISSE-6

MISSE-5 Environmental Exposure for one year

- $\sim 1.8 \times 10^{20} \text{ atoms/cm}^2 \text{ atomic oxygen}$
- ~ 525 equivalent sun-hours UV
- >6,500 thermal cycles of +40/-40 °C






Left to right, AMJ600IR, AZ93, AMJ700IBU on beta cloth, AMJ760/AMJ750, TMS800IY/TMJ-20LSB screen printed on Dutch glass cloth



# Marker Coatings - AMJ600IR




Flight Ram-facing

Control



# Marker Coatings - AMJ700IBU



Flight Wake-facing

Control



# Marker Coatings - AMJ760/AMJ750




Flight Ram-facing

Control



# Marker Coatings - TMS800IY/TMJ-20LSB




Flight Ram-facing

Control



# MISSE-6 TMJ-20-LSB on Dutch Glass Cloth





## **Conclusions**

- ◆ Coatings, particularly AZ93 zinc oxide pigment with inorganic binder, held up well in LEO {AO+UV} environment.
- No evidence of significant contamination.
- ♦ Marker / Label coatings maintained their color.
- ♦ Beta cloth darkened due to UV exposure. Solar absorptance was in agreement with previous MISSE exposure.
- ◆ Dutch glass cloth darkened slightly due to UV exposure.



#### **MISSE-7 and MISSE-8**

- ◆ Continuing to fly AZ93 as contamination monitor on both MISSE-7 and MISSE-8.
- ♦ MISSE-7
  - ◆ AZ-400, AZ-2000-LSW, AZW/LAII, RM550IB on aluminum
  - ◆ AZ-3700 on Kapton with 3M 966 adhesive
- ♦ MISSE-8
  - ♦ AZ-400, AZ-2000-ICW, AZ-2000-LSW, AZ-2100-IECW white coatings
  - ◆ AZ-3700 metallic coating
  - ◆ MLS-85-SB-C, RM-550-LSB, RM-550-LSB-H, RM-550-LSB-C, RM-550-IB black coatings



## Acknowledgments

- Julie Henkener, system manager, Rajib Dasgupta, previous system manager, and Dr. John Alred, deputy system manager for ISS M&P
- Dr. Gary Pippin, Boeing Research & Technology, for estimated environmental exposures.
- Bill Kinard, MISSE chief scientist (retired), Karen Gibson, Ray Seals, and Sandie Gibbs, LaRC
- Beth Cook and Twila Schneider, Advanced Materials for Exploration program